



## DECO HARMONY YELLOW 7945 R FR

### Product information

Application	Inside
System	Rolling
Feature	Decorative Climate Screens
Flame retardant	Yes
Material	Polyolefin 77%, Polyester 23%
Warranty	Warranty five (5) years under all types of greenhouse covering. See Svensson's limited warranty for all terms, conditions and exclusions in writing. This screen is tested for colour fastness in accordance with EN ISO 105-B02. Any and all liability for colour changes of the screen that are not assessable pursuant to EN ISO 105-B02 is excluded. Svensson assumes no liability for any unforeseen effects on the crop due to colour alterations of the light.

Properties	Value	Unit	Test Methods
Shading level in diffused light PAR**	81	%	Svensson method
Shading level in direct light PAR**	79	%	Svensson method
Energy saving	45	%	Svensson method
Width of strips	4.6	mm	
Color fastness	7-8	(Scale 1-8)	Against light according to EN ISO 105-B02
Elongation (length / width) *	52/30	%	According to ISO 13934-1
Tensile strength (length/width) *	698/452	N/5cm	According to ISO 13934-1

\* Width 50 mm

\*\* PAR = 400 - 700 nm, accuracy +/- 1%

\*\*\* UV-light = 300 - 400 nm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, Svensson does not accept any liability in respect of its accuracy.

Further information concerning the product and its installation may be obtained from Svensson and its authorized distributors. Svensson's products and names are protected by patent and other intellectual property rights.

Products marked FR are flame retardant. No other products delivered by Svensson are flame retardant.

AB Ludvig Svensson is an ISO 14001/90001 certified company.