



## GROUNDCOVER 100 BLACK SQUARED

### Product information

Application	Inside
Feature	Weed control
Flame retardant	No
Material	Polyolefin 100%
Pattern	Length direction: a blue line every 25 cm. Width direction: a red / orange line every 12.5 cm.
Warranty	Resistant to UV-radiation according to ISO 4892-3 cycle 3 (based on QUV test min. 7400 hours (cycles of 5 hours exposure to UV-A light 340 nm 0.83 W/m <sup>2</sup> at 50°C and 1 hour water spray), which theoretically corresponds to a UV-radiation of 800 kLy.

Properties	Value	Unit	Test Methods
Weight	100	g/m <sup>2</sup>	
Water permeability	10	l/m <sup>2</sup> /s	According to ISO 11058
Tensile strength (length/width) *	850 / 700	N/5cm	According to ISO 13934-1

\* Width 50 mm

\*\* PAR = 400 - 700 nm, accuracy +/- 1%

\*\*\* UV-light = 300 - 400 nm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, Svensson does not accept any liability in respect of its accuracy.

Further information concerning the product and its installation may be obtained from Svensson and its authorized distributors. Svensson's products and names are protected by patent and other intellectual property rights.

Products marked FR are flame retardant. No other products delivered by Svensson are flame retardant.

AB Ludvig Svensson is an ISO 14001/90001 certified company.