




HELLO
Upholstery fabrics


 **svensson**




3062



3125



3326




3363




3544




3733




4271




4362




4443



4452



4461




4534



4644




4845



5041




5345



5672



5744



5931



6144

HELLO

Upholstery fabrics

Width: 140 cm

Weight: 280 g/m²

Material: Trevira CS 100%

Shrinkage: 2 %

Color fastness:

Against dry rubbing according to

EN ISO 105-X12:

- 4 (Scale 1-5)

Against light according to EN ISO 105-B02

- 5-7 (Scale 1-8)

Against wet rubbing according to

EN ISO 105-X12:

- 3-4 (Scale 1-5)

Abrasion resistance:

Martindale (According to EN ISO 12947-2):

- 50000 rubs

Flame retardancy:

- EN ISO 1021 1, 2- DIN 4102-1

B1- IMO FTP Code 2010:

- DIN 4102-1 B1

- IMO FTP Code 2010: Part 8

- BS 5852 crib 5

- NF P 92-503-507, M1

- UNI 9175, 1 IM

- SN 198898

- NFPA 260

- EN 13501-1, B-s1 d0

Care instructions:



For further information:


Svensson
511 82 Kinna, Sweden

T: +46 320 20 92 00


F: +46 320 21 10 10

E: info@ludvigsvensson.com







6442




6453




6530




6540




6570



6621




6631




6634




6662



6740




6742




6760




6943




8200




8300




8400




8500



8550



8700



8900

HELLO

Upholstery fabrics

Width: 140 cm

Weight: 280 g/m²

Material: Trevira CS 100%

Shrinkage: 2 %

Color fastness:

Against dry rubbing according to

EN ISO 105-X12:

- 4 (Scale 1-5)

Against light according to EN ISO 105-B02

- 5-7 (Scale 1-8)

Against wet rubbing according to

EN ISO 105-X12:

- 3-4 (Scale 1-5)

Abrasion resistance:

Martindale (According to EN ISO 12947-2):

- 50000 rubs

Flame retardancy:

- EN ISO 1021 1, 2- DIN 4102-1

B1- IMO FTP Code 2010:

- DIN 4102-1 B1

- IMO FTP Code 2010: Part 8

- BS 5852 crib 5

- NF P 92-503-507, M1

- UNI 9175, 1 IM

- SN 198898

- NFPA 260

- EN 13501-1, B-s1 d0

Care instructions:



For further information:

Svensson
511 82 Kinna, Sweden

T: +46 320 20 92 00

F: +46 320 21 10 10

E: info@ludvigsvensson.com

