



## OBSCURA 10070 R FR W

### Product information

Application	Inside
System	Rolling
Feature	Light deprivation / blackout, Energy saving
Flame retardant	Yes
Material	Polyolefin 100%
Pattern	Laminated
Warranty	Please, contact your Svensson representative for warranty information.

Properties	Value	Unit	Test Methods
Shading level in diffused light PAR**	99.9	%	Svensson method
Shading level in direct light PAR**	99.9	%	Svensson method
Energy saving	70	%	Svensson method
Thickness	0.4	mm	
Elongation (length / width) *	15/17	%	According to ISO 13934-1
Tensile strength (length/width) *	1339/1334	N/5cm	According to ISO 13934-1

\* Width 50 mm

\*\* PAR = 400 - 700 nm, accuracy +/- 1%

\*\*\* UV-light = 300 - 400 nm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, Svensson does not accept any liability in respect of its accuracy.

Further information concerning the product and its installation may be obtained from Svensson and its authorized distributors. Svensson's products and names are protected by patent and other intellectual property rights.

Products marked FR are flame retardant. No other products delivered by Svensson are flame retardant.

AB Ludvig Svensson is an ISO 14001/90001 certified company.