






KHAKI
Upholstery fabrics




3035



3044




3234




3236



3550




3617




3651




3745




3952




4163




4360



4372



4433




4444




4452




4550



4554



4653



4745



4760

KHAKI

Upholstery fabrics

Breite: 140 cm

Gewicht: 360 G/M²

Material: Trevira CS 100%

Einlaufen: 2 %

Color fastness:

Against dry rubbing according to

EN ISO 105-X12:

- 4-5 (Scale 1-5)

Gegen Licht nach EN ISO 105-B02

- 5-7 (Skala 1-8)

Against wet rubbing according to

EN ISO 105-X12:

- 4 (Scale 1-5)

Scheuerfestigkeit:

Martindale (Nach: EN ISO 12947-2):

- 50000 Touren

Schwerentflammbarkeit:

- EN 1021 part 1, 2- DIN 4102-1

B1- IMO FTP Code 2010:

- DIN 4102-1 B1

- IMO FTP Code 2010: Part 8

- BS 5852 Crib 5

- BS 5867-2 Type B

- NF P 92 503-507, M1

- EN 13773, Class 1

- FAR/JAR/CS 25.853

- FMVSS 302

- EN 13501-1

Wartungsanweisungen:



For further information:

Svensson


511 82 Kinna, Sweden

T: +46 320 20 92 00

F: +46 320 21 10 10

E: info@ludvigsvensson.com







5445




5451




5535




5863




6043



6235



6252




6272




6544




6560



6662



6750



6835



6841



8500

KHAKI

Upholstery fabrics

Breite: 140 cm

Gewicht: 360 G/M²

Material: Trevira CS 100%

Einlaufen: 2 %

Color fastness:

Against dry rubbing according to

EN ISO 105-X12:

- 4-5 (Scale 1-5)

Gegen Licht nach EN ISO 105-B02

- 5-7 (Skala 1-8)

Against wet rubbing according to

EN ISO 105-X12:

- 4 (Scale 1-5)

Scheuerfestigkeit:

Martindale (Nach: EN ISO 12947-2):

- 50000 Touren

Schwerentflammbarkeit:

- EN 1021 part 1, 2- DIN 4102-1

B1- IMO FTP Code 2010:

- DIN 4102-1 B1

- IMO FTP Code 2010: Part 8

- BS 5852 Crib 5

- BS 5867-2 Type B

- NF P 92 503-507, M1

- EN 13773, Class 1

- FAR/JAR/CS 25.853

- FMVSS 302

- EN 13501-1

Wartungsanweisungen:



For further information:

Svensson
511 82 Kinna, Sweden

T: +46 320 20 92 00

F: +46 320 21 10 10

E: info@ludvigsvensson.com

