



GROUNDCOVER 130 BLACK SQUARED

Product information

| | |
|-----------------|--|
| Application | Inside |
| Feature | Weed control |
| Flame retardant | No |
| Material | Polyolefin 100% |
| Pattern | Length direction: a white line every 25 cm. Width direction: a white line every 25 cm. |
| Warranty | Resistant to UV-radiation according to ISO 4892-3 cycle 3 (based on QUV test min. 7400 hours (cycles of 5 hours exposure to UV-A light 340 nm 0.83 W/m ² at 50°C and 1 hour water spray), which theoretically corresponds to a UV-radiation of 800 kLy. The warranty is no longer valid if the products have been in contact with sulphur-, chlorine-, iron-, and bromine derivates, as well as copper sulfates. |

| Properties | Value | Unit | Test Methods |
|-----------------------------------|------------|---------------------|--------------------------|
| Weight | 130 | g/m ² | |
| Water permeability | 10 | l/m ² /s | According to ISO 11058 |
| Tensile strength (length/width) * | 1100 / 900 | N/5cm | According to ISO 13934-1 |

* Width 50 mm

** PAR = 400 - 700 nm, accuracy +/- 1%

*** UV-light = 300 - 400 nm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, Svensson does not accept any liability in respect of its accuracy.

Further information concerning the product and its installation may be obtained from Svensson and its authorized distributors. Svensson's products and names are protected by patent and other intellectual property rights.

Products marked FR are flame retardant. No other products delivered by Svensson are flame retardant.

AB Ludvig Svensson is an ISO 14001/90001 certified company.