



HARPER
Upholstery fabrics



3034



3070



3122



3325



3335



3522



3540



3671




4332



4344



4422



4520



4533




4621




4652



5431



5471



5851



5921



6333

HARPER

Upholstery fabrics

Width: 140 cm

Weight: 365 g/m²

Material: Trevira CS 100%

Shrinkage: 2 %

Color fastness:

Against dry rubbing according to

EN ISO 105-X12:

- 4-5 (Scale 1-5)

Against light according to EN ISO 105-B02

- 5-7 (Scale 1-8)

Against wet rubbing according to

EN ISO 105-X12:

- 3-4 (Scale 1-5)

Abrasion resistance:

Martindale (According to EN ISO

12947-2):

- 85000 rubs

Flame retardancy:

- DIN 4102-1 B1- IMO FTP Code 2010:

- IMO FTP Code 2010: Part 8

- NF P 92 503-507, M1

- BS 5852 Crib 5

- UNI 9175, 1 IM

- EN 13501-1, B-s1, d0

- TB 117

- NFPA 260

- SN 198898

- BS 5867-2 Type B

Care instructions:



For further information:


Svensson
511 82 Kinna, Sweden

T: +46 320 20 92 00

F: +46 320 21 10 10

E: info@ludvigsvensson.com





6452




6625



6632



6861



6931

HARPER

Upholstery fabrics

Width: 140 cm

Weight: 365 g/m²

Material: Trevira CS 100%

Shrinkage: 2 %

Color fastness:

Against dry rubbing according to

EN ISO 105-X12:

- 4-5 (Scale 1-5)

Against light according to EN ISO 105-B02

- 5-7 (Scale 1-8)

Against wet rubbing according to

EN ISO 105-X12:

- 3-4 (Scale 1-5)

Abrasion resistance:

Martindale (According to EN ISO 12947-2):

- 85000 rubs

Flame retardancy:

- DIN 4102-1 B1- IMO FTP Code 2010:

- IMO FTP Code 2010: Part 8

- NF P 92 503-507, M1

- BS 5852 Crib 5

- UNI 9175, 1 IM

- EN 13501-1, B-s1, d0

- TB 117

- NFPA 260

- SN 198898

- BS 5867-2 Type B

Care instructions:



For further information:

Svensson
511 82 Kinna, Sweden

T: +46 320 20 92 00

F: +46 320 21 10 10

E: info@ludvigsvensson.com

