





JOLLY RE
Upholstery fabrics




3031



3132



3236



3245



3327



3518



3872



4370



4433




4454



4544




5221




5852




6133




6231




6272




6424



6542



6621



6635

JOLLY RE

Upholstery fabrics

Bredd: 140 cm**Vikt:** 330 g/m²**Material:** Återvunnen Trevira CS 72%
Trevira CS 28%**Krympning:** 2 %**Färghårdighet:***Mot gnidning torr enligt EN ISO 105-X12:*

- ≥ 4 (Skala 1-5)

Mot ljus enligt EN ISO 105-B02

- ≥ 5 - 7 (Skala 1-8)

Mot gnidning våt enligt EN ISO 105-X12:

- ≥ 3-4 (Skala 1-5)

Nötning:*Martindale (Enligt EN ISO 12947-2):*
- 40000 varv**Svårantändlighet:**

- EN 1021-1&2 - DIN 4102-1

B1- BS 5852 Crib 5- EN 13501-1;

B-s1, d0- NFP 92-503-507 M1- IMO

FTP Code 2010:

- DIN 4102-1 B1

- BS 5852 Crib 5

- EN 13501-1; B-s1, d0

- NFP 92-503-507 M1

- IMO FTP Code 2010: Part 8


Skötselanvisning:**For further information:**Svensson
511 82 Kinna, Sweden

T: +46 320 20 92 00

F: +46 320 21 10 10

E: info@ludvigsvensson.com





6754




6931



8110



8330



8900

JOLLY RE

Upholstery fabrics

Bredd: 140 cm

Vikt: 330 g/m²

Material: Återvunnen Trevira CS 72% - 40000 varv
Trevira CS 28%

Krympning: 2 %

Färghårdighet:

Mot gnidning torr enligt EN ISO 105-X12:

- ≥ 4 (Skala 1-5)

Mot ljus enligt EN ISO 105-B02

- ≥ 5 - 7 (Skala 1-8)

Mot gnidning våt enligt EN ISO 105-X12:

- ≥ 3-4 (Skala 1-5)

Nötning:

Martindale (Enligt EN ISO 12947-2):

- 40000 varv

Svårantändlighet:

- EN 1021-1&2 - DIN 4102-1

B1- BS 5852 Crib 5- EN 13501-1;

B-s1, d0- NFP 92-503-507 M1- IMO

FTP Code 2010:

- DIN 4102-1 B1

- BS 5852 Crib 5

- EN 13501-1; B-s1, d0

- NFP 92-503-507 M1

- IMO FTP Code 2010: Part 8

Skötselanvisning:



For further information:

Svensson
511 82 Kinna, Sweden

T: +46 320 20 92 00

F: +46 320 21 10 10

E: info@ludvigsvensson.com

