







POPPY
Upholstery fabrics



3034



3236



3372



3443



3518



3554



4352



4372




4442




5245



5350



5431




5936



6236



6272




6444



6527



6562



6612



6635

POPPY

Upholstery fabrics

Bredd: 150 cm

Vikt: 355 g/m²

Material: Trevira CS 100%

Krympning: 2 %

Färghårdighet:

Mot gnidning torr enligt EN ISO 105-X12:

- 4-5 (Skala 1-5)

Mot ljus enligt EN ISO 105-B02

- 5-7 (Skala 1-8)

Mot gnidning våt enligt EN ISO 105-X12:

- 4 (Skala 1-5)

Nötning:

Martindale (Enligt EN ISO 12947-2):

- 50000 varv

Svårantändlighet:

- EN 1021 part 1, 2- DIN 4102-1

B1- IMO FTP Code 2010:

- DIN 4102-1 B1

- IMO FTP Code 2010: Part 8

- NF P 92 503-507, M1

- BS 5852 Crib 5

- BS 5867-2 Type B

- TB117 2013

- EN 13501-1

- NFPA 260

Skötselanvisning:



For further information:


Svensson
511 82 Kinna, Sweden

T: +46 320 20 92 00


F: +46 320 21 10 10

E: info@ludvigsvensson.com





6642




6731




6733



6920



6932




6953



8200



8700



8800

POPPY

Upholstery fabrics

Bredd: 150 cm

Vikt: 355 g/m²

Material: Trevira CS 100%

Krympning: 2 %

Färghårdighet:

Mot gnidning torr enligt EN ISO 105-X12:

- 4-5 (Skala 1-5)

Mot ljus enligt EN ISO 105-B02

- 5-7 (Skala 1-8)

Mot gnidning våt enligt EN ISO 105-X12:

- 4 (Skala 1-5)

Nötning:

Martindale (Enligt EN ISO 12947-2):

- 50000 varv

Svårantändlighet:

- EN 1021 part 1, 2- DIN 4102-1

B1- IMO FTP Code 2010:

- DIN 4102-1 B1

- IMO FTP Code 2010: Part 8

- NF P 92 503-507, M1

- BS 5852 Crib 5

- BS 5867-2 Type B

- TB117 2013

- EN 13501-1

- NFPA 260

Skötselanvisning:



For further information:

Svensson
511 82 Kinna, Sweden

T: +46 320 20 92 00

F: +46 320 21 10 10

E: info@ludvigsvensson.com

