

GRAIN
Hanging fabrics

svensson


3032



3040


3310


3325


3360


3524



3560


3631


3871



4021


4333


4340


4362



4421


4472


4510


4533


4552


4554


4641

GRAIN
Hanging fabrics

Width: 300 cm
Weight: 190 g/m²
Material: Trevira CS 100%
Shrinkage: 2 %

Color fastness:
Against light according to EN ISO 105-B02
- ≥ 5-7 (Scale 1-8)

Against washing according to EN ISO 105-C06
- ≥ 5 (Scale 1-5)

Flame retardancy:
- *BS 5867:*
- DIN 4102-1 class B1
- IMO FTP Code Part 7
- UNI 9177, Class 1
- EN 13773, Class 1
- EN 13501-1, B-s1, d0
- NFPA 701
- UNI 8456/8457

Acoustics:
Measurement of sound absorption in a reverberation room: EN ISO 354:2003.Ration of sound absorption EN ISO 11654:1997: w = 0,60, Class C

Care instructions:



For further information:

Svensson
511 82 Kinna, Sweden

T: +46 320 20 92 00
F: +46 320 21 10 10
E: info@ludvigsvensson.com


4645


5040


5060


5431


6042


6222


6235


6423


6450

6510


6521


6530


6540


6630


6635


6780


6820


6930

8000


8500

GRAIN
Hanging fabrics

Width: 300 cm
Weight: 190 g/m²
Material: Trevira CS 100%
Shrinkage: 2 %

Color fastness:
Against light according to EN ISO 105-B02
- ≥ 5-7 (Scale 1-8)

Against washing according to EN ISO 105-C06
- ≥ 5 (Scale 1-5)

Flame retardancy:
- *BS 5867:*
- DIN 4102-1 class B1
- IMO FTP Code Part 7
- UNI 9177, Class 1
- EN 13773, Class 1
- EN 13501-1, B-s1, d0
- NFPA 701
- UNI 8456/8457

Acoustics:
Measurement of sound absorption in a reverberation room: EN ISO 354:2003.Ration of sound absorption EN ISO 11654:1997: w = 0,60, Class C

Care instructions:



For further information:

Svensson
511 82 Kinna, Sweden

T: +46 320 20 92 00
F: +46 320 21 10 10
E: info@ludvigsvensson.com