





HARMONY 6920 O E

Product information

Exterior **Application** System Rolling, Sliding

Solar control, Light diffusion Feature

Flame retardant

Material Polyolefin 100%

Pattern 1 white / black, 1 white diffuse, 1 white / black, 1 open

Warranty five (5) years under all types of greenhouse covering and three (3) years for outdoor use. See Svensson's limited warranty for all terms, conditions and exclusions in writing. Warranty

Properties	Value	Unit	Test Methods
Shading level in diffused light PAR**	75	%	Protocol NEN 2675
	72	%	Svensson method
Shading level in direct light PAR**	72	%	Protocol NEN 2675
	69	%	Svensson method
Energy saving	20	%	Svensson method
Width of strips	4	mm	
Weight	138	g/m²	

^{*} Width 50 mm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, Svensson does not accept any liability in respect of its accuracy.

Further information concerning the product and its installation may be obtained from Svensson and its authorized distributors. Svensson's products and names are protected by patent and other intellectual property rights.

Products marked FR are flame retardant. No other products delivered by Svensson are flame retardant.

AB Ludvig Svensson is an ISO 14001/90001 certified company.

^{**} PAR = 400 - 700 nm, accuracy +/- 1%

^{***} UV-light = 300 - 400 nm