






STEP

Upholstery fabrics



150




186




222




240



260




290




550




559



570




609



650




670




690




708




711




750




760



789



811



850

STEP

Upholstery fabrics

Width: 140 cm

Weight: 410 g/m²

Material: Wool 75%
Viscose 25%

Color fastness:

Against dry rubbing according to

EN ISO 105-X12:

- 4-5 (Scale 1-5)

Against light according to EN ISO

105-B02

- 5-7 (Scale 1-8)

Against wet rubbing according to

EN ISO 105-X12:

- 3-4 (Scale 1-5)

Abrasion resistance:

Martindale (According to EN ISO

12947-2):

- 50000 rubs

Flame retardancy:

- BS 5852, Crib 5

- TB 117

- IMO FTP Code Part 8 (IMO Res.

A.652 (16)

- UNI 9175, 1 IM

Care instructions:



For further information:


Svensson
511 82 Kinna, Sweden

T: +46 320 20 92 00

F: +46 320 21 10 10

E: info@ludvigsvensson.com







860




870



886



888



900



990

STEP

Upholstery fabrics

Width: 140 cm
Weight: 410 g/m²
Material: Wool 75%
 Viscose 25%

Color fastness:
Against dry rubbing according to EN ISO 105-X12:
 - 4-5 (Scale 1-5)
Against light according to EN ISO 105-B02
 - 5-7 (Scale 1-8)
Against wet rubbing according to EN ISO 105-X12:
 - 3-4 (Scale 1-5)

Abrasion resistance:
Martindale (According to EN ISO 12947-2):
 - 50000 rubs

Flame retardancy:
 - BS 5852, Crib 5
 - TB 117
 - IMO FTP Code Part 8 (IMO Res. A.652 (16)
 - UNI 9175, 1 IM

Care instructions:



For further information:

Svensson
 511 82 Kinna, Sweden

T: +46 320 20 92 00
 F: +46 320 21 10 10
 E: info@ludvigsvensson.com

